



- (A) _____
LOWER LEVEL TO UPPER LEVEL WALKING/WORKING HEIGHT
- (B) _____
WALL SUBSTRATE TYPE (IE: BRICK, CONCRETE BLOCK, METAL SIDING, ETC)
- (C) _____
WALL TO CENTERLINE OF LADDER. OSHA 1910.27(C)(4) STATES THAT THE DISTANCE FROM THE CENTERLINES OF THE RUNGS TO THE NEAREST PERMANENT OBJECT SHALL NOT BE LESS THAN 7". OSHA ALSO REQUIRES A PLATFORM IF THE DISTANCE EXCEEDS 12". PLEASE STATE WIDTH OF ANY GUTTER OR OBJECT. (E.G GUTTER 9" WIDE). FIXFAST WILL ENSURE THE CORRECT BRACKET IS SUPPLIED.
- (D) _____
FLOOR SUBSTRATE TYPE (IE, ROOF MEMBRANE, CONCRETE, METAL ROOF, ETC)

PROJECT REF: _____
 CONTRACTOR: _____
 APPROVED BY: _____
 SIGN HERE: _____

| AVAILABLE LADDER KITS | |
|-----------------------|---------------|
| CODE | HEIGHTS UP TO |
| RL33.53 | 53" (4' 5") |
| RL33.100 | 100" (8'4") |
| RL33.147 | 147" (12' 3") |
| RL33.195 | 195" (16' 3") |
| RL33.240 | 240" (20') |

| REVISIONS | | | | |
|-----------|------------|----|-----|----------------------------|
| Rev | Date | By | Rep | Remarks |
| 1 | 3/05/2016 | WY | RP | Released to manufacturing |
| 2 | 30/06/2016 | WY | RP | Revise as Per W.L Comments |

FIXFAST USA

Maximum safety. Minimum fuss.

FIXFAST USA
 6210S Indianapolis Road
 Whitestown IN 46075 USA
 Tel:- +1 317 769 7710
 Fax:- +1 317 769 5560
 Email:- technical@fixfastusa.com
 Web:- www.fixfastusa.com

FIXFAST USA CONFIDENTIAL MATERIAL

THIS DRAWING IS THE PROPERTY OF 'FIXFAST USA' AND SHALL NOT BE COPIED OR DISCLOSED TO A THIRD PARTY IN WHOLE OR PART WITHOUT THE CONSENT IN WRITING OF 'FIXFAST USA'.

| | | | |
|---|---------|----------------------------|-----|
| Description Standard Access Ladder With Lead On Handrails | | | |
| Material | | | |
| Product Code RL33 SERIES | FAB No. | Drawing No. 7099 | Rev |