



- (A) LOWER LEVEL TO UPPER LEVEL WALKING/WORKING HEIGHT
- (B) WALL SUBSTRATE TYPE (IE: BRICK, CONCRETE BLOCK, METAL SLIDING, ETC)
- (C) WALL TO CENTERLINE OF LADDER. OSHA 1910.27(C)(4) STATES THAT THE DISTANCE FROM THE CENTERLINES OF THE RUNGS TO THE NEAREST PERMANENT OBJECT SHALL NOT BE LESS THAN 7". OSHA ALSO REQUIRES A PLATFORM IF THE DISTANCE EXCEEDS 12". PLEASE STATE WIDTH OF ANY GUTTER OR OBJECT. (E.G. GUTTER 9" WIDE). FIXFAST WILL ENSURE THE CORRECT BRACKET IS SUPPLIED
- (D) FLOOR SUBSTRATE TYPE (IE. ROOF MEMBRANE, CONCRETE, METAL ROOF, ETC)

PROJECT REF: \_\_\_\_\_  
 CONTRACTOR: \_\_\_\_\_  
 APPROVED BY: \_\_\_\_\_  
 SIGN HERE: \_\_\_\_\_

AVAILABLE LADDER KITS	
CODE	HEIGHTS UP TO
RL23.53	53" (4' 5")
RL23.100	100" (8' 4")
RL23.147	147" (12' 3")

REVISIONS					
Rev	Date	By	Rep	Remarks	
1	8/06/2016	RP	WL	Released	
2	30/06/2016	RP	WL	Released	

**FIXFAST USA**

Maximum safety. Minimum fuss.

FIXFAST USA  
 6210S Indianapolis Road  
 Whitestown IN 46075 USA  
 Tel:- +1 317 769 7710  
 Fax:- +1 317 769 5560  
 Email:- technical@fixfastusa.com  
 Web:- www.fixfastusa.com

**FIXFAST USA CONFIDENTIAL MATERIAL**

THIS DRAWING IS THE PROPERTY OF  
 'FIXFAST USA' AND SHALL NOT BE COPIED  
 OR DISCLOSED TO A THIRD PARTY IN  
 WHOLE OR PART WITHOUT THE CONSENT  
 IN WRITING OF 'FIXFAST USA'.

Description <b>Mini Fixed Ladder With Lead On Handrails</b>			
Material			
Product Code <b>RL23 SERIES</b>	FAB No.	Drawing No. <b>7120</b>	Rev